


SLEEVED PLUG VALVES ORDERING INSTRUCTIONS



Size
Range available from 1/2" to 24"
Refer to catalog for Class availability

Port
R Reduced
F Full

Class
15 Class 150 lbs
30 Class 300 lbs
60 Class 600 lbs

Flow
2 2-Way
3 3-Way

End Connection
F Flanged Raised Face
FF Flanged Flat Face
SE Screwed
SW Socket Weld
X Screwed x Socket Weld
BW Butt Weld
S Special

Operator
B Bare Stem
EG Enclosed Gear
EGL Enclosed Gear + Locking Device
W Wrench
WL Wrench + Locking Device

Flow Pattern (Leave blank for 2-Way)
FA1, FA2, FA3, FA4, FA5
Refer to catalog for Flow Patterns

Body Material
Refer to Body & Plug Material Table

Plug Material
Refer to Body & Plug Material Table

Sleeve Material
A PFA
G GF2P
P PTFE
R RTFE
U UHMWPE
Z Hi-Temp Teflon®

Special
(A combination of Specials can be used)
CL Prepared for Chlorine Service
DBB Double Block & Bleed
FE Severe Service
HF HF Alky HydroFluoric Acid
OX Prepared for Oxygen Service

Options
(A combination of Options can be used)
CCV Cage Control Valve
EZ EZ-Seal®
FJ Full Jacket
FS Fire Seal
PJ Partial Jacket
S Special (Description required)
V6 V-Port 60°
VN Vented Plug (Specify location and diameter)
U Upstream
D Downstream
B Bottom

Example for Vented Plug: VN (U, B, 1/4")
Note: HF, FS, CL are vented by default, refer to catalog for details

BODY & PLUG MATERIAL TABLE

CODE	DESCRIPTION	ASTM DESIGNATION
DI	Ductile Iron	ASTM A395
WCB	Carbon Steel	ASTM A216 WCB
LCB	Carbon St. Low Temp.	ASTM A352
304	304 Stainless Steel	ASTM A351 CF8
304L	304L Stainless Steel	ASTM A351 CF3
316	316 Stainless Steel	ASTM A351 CF8M
316L	316L Stainless Steel	ASTM A351 CF3M
317	317 Stainless Steel	ASTM A351 CG8M
317L	317L Stainless Steel	ASTM A351 CG3M
A20	Alloy 20	ASTM A351 CN7M
B61	Bronze	ASTM B61
CD4	CD4MCu	ASTM A351 CD2MCu
HB	HASTELLOY® B	ASTM A494 N7M
HB2	HASTELLOY® B 2	ASTM A494 N12MV
HC	HASTELLOY® C	ASTM A494 CW6M
??	HASTELLOY® ???	ASTM A949 CW12MW
I600	INCONEL®	ASTM A494 CY40
NI	Nickel	ASTM A494 M-35-1
MO	MONEL®	ASTM A494 M-35-1
NAB	NI-Al-Bronze	ASTM B148 C958
TC3	Titanium	ASTM B367 Gr. C3
TC5	Titanium	ASTM B367 Gr. C5*
ZC2	Zirconium	ASTM B752 Gr. 702C
ZC5	Zirconium	ASTM B752 Gr. 705C

* FluoroSeal Inc. Special C5 Proprietary Heat Treatment Process
Other and Special Alloys Available on Request

PLUG-ANSI-R001-2007